

Model 410i-D Standard Range CO₂ Analyzer

Based on Non-Dispersive Infrared (NDIR) principle with enhanced communication capabilities for source emissions monitoring



Key Features

- ◆ Ethernet connectivity for efficient remote access
- ◆ Enhanced user interface with one button programming and large display screen
- ◆ Flash memory for increased data storage and user downloadable software
- ◆ Enhanced electronics design optimizes product commonality
- ◆ Improved layout for easier accessibility to components

A change is in the air
The industry's new best-of-breed. Our customers told us exactly what they're looking for in a gas monitoring solution: reliability, simplicity, ease of use. The new *iSeries* platform delivers on all counts - and then goes a step farther. A core product in Thermo's new *iSeries* product line is the Model 410i-D NDIR CO₂ analyzer.

Using new optical filter technology, the Model 410i-D is designed to monitor and report on CO₂ stack gas levels utilizing either of the accepted industry standard sampling methods, Straight Extractive Sampling or Dilution Sampling. The gas detection scheme uses optically fixed bandpass interference filters and quantum detection to analyze the gas stream, leading to a superior level of performance and

reliability. Add to that, an expanded ambient temperature operating range and these instruments provide excellent performance over a wider range of concentrations.

This state-of-the-art gas analyzer offers features such as an ethernet port as well as flash memory for increased data storage.

Ethernet connectivity provides efficient remote access, allowing the user to download measurement information directly from the instrument without having to be on-site.

You can easily program soft-keys to allow you to jump directly to frequently accessed functions, menus or screens. The larger interface screen can display up to five lines of measurement information while primary screen remains visible.

Comprehensive Service Solutions

To maintain optimal product performance, you need immediate access to experts worldwide, as well as priority status when your air quality equipment needs repair or replacement. Thermo Electron offers comprehensive, flexible support solutions for all phases of the product lifecycle. Through predictable, fixed-cost pricing, Thermo services help protect the return on investment and total cost of ownership of your Thermo Electron air quality products.

Product Specifications

Preset Ranges	0-200, 500, 1000, 2000, 5000, and 10000 ppm
Custom Ranges	0-200 to 10000 ppm
Zero Noise	0.1 ppm RMS (300 second averaging time)
Minimum Detectable	0.2 ppm (300 second averaging time)
Zero Drift	<0.20 ppm - 7 Days
Span Drift	< 0.5% Reading - 24 Hours <1% Reading - 7 Days
Response Time	90 seconds (30 second average time)
Precision	+/-1.0% of reading
Linearity	+/-1.0% of span (at concentrations of 10% to 100% of span)
Sample Flow Rate	1.0 liter per minute
Operating Temperature	+5 ⁰ C to +45 ⁰ C
Power Requirements	100 vac, 115 vac, 220-240 vac +/-10% @ 275W
Size and Weight	16.75"(W) x 8.62"(H) x 23"(D), 39 lbs. (17.7 kg)
Outputs	Selectable Voltage, RS232/RS485, TCP/IP, 10 Status Relays, and Power Fail Indication (standard). 0-20 or 4-20 mA Isolated Current Outout (optional)
Inputs	16 Digital Inputs (standard), 8 0-10Vdc Analog Inputs (optional)

Ordering Information

Model 410i-D CO₂ Analyzer

Choose from the following configurations/options to customize your own Model 410i:

Voltage options:

A = 120 Vac 50/60 Hz
B = 220 Vac 50/60 Hz
J = 100 Vac 50/60 Hz

Internal zero / span:

N = No zero / span valve
Z = Internal zero span assembly

Filter Wheel Purge:

P = Filter wheel purge setup (standard)

Sample Gas Concentration

D = 0 - 10,000 ppm

Optional I/O:

A = No optional I/O (standard)
C = 0-20, 4-20mA current output - 6 channels, 0-10v analog input - 8 channels

Mounting hardware:

A = Bench mounting (standard)
B = Ears & handles, EIA
C = Ears & handles, retrofit

Your Order Code: 410iD - _ _ _ D _ _ _

Other options:

- Teflon particulate filter
- Rack mounts
- Rear extender



This specification sheet is for informational purposes only and is subject to change without notice. Thermo makes no warranties, expressed or implied, in this product summary. © 2005 Thermo Electron Corporation. All rights reserved. Thermo Electron Corporation, Analyze. Detect. Measure. Control are trademarks of Thermo Electron Corporation

Lit_410i_StdEID_06/07

Thermo
ELECTRON CORPORATION

Environmental Instruments

Air Quality Instruments

www.thermo.com/air

27 Forge Parkway
Franklin, MA 02038 USA

Takkebijsters 1
Breda, BL 4817
The Netherlands

+1 (866) 282-0430
+1 (508) 520-1460 fax

+33 (0) 76 5879888
+33 (0) 76 5816520 fax